

# UHD SIGNAGE



## QMD

- Slim & Light Design
- Multiple Connectivity
- FHD 4 PBP Support



## QMD-BR

- All-in-One Display
- IR Touch
- Slim Design
- FHD 4 PBP Support



## QMF

- Full Size Availability
- Non-Glare Panel
- Seamless Design
- Various Connectivity




### LIFELIKE IMAGE PRESENTATION

Make high-detail visuals visible with the smallest details for a hyper-realistic and immersive visual experiences.



### UHD SBB SUPPORT

Empower UHD streaming through SBB compatibility



### PIVOT MODE SUPPORT

Customize installation to fit location aesthetics

# SPECIFICATIONS

## | UHD SIGNAGE

SERIES		QMD-BR	QMD	QMF		
Size		85"	85"	49" / 55" / 65"	75"	98"
Resolution		3840x2160(16:9)	3840x2160(16:9)	3840x2160 (16:9)	3840x2160 (16:9)	3840x2160 (16:9)
Brightness(Typ.)		430cd/m <sup>2</sup> (With Touch Glass)	500cd/m <sup>2</sup>	500cd/m <sup>2</sup>	500cd/m <sup>2</sup>	500cd/m <sup>2</sup>
Contrast Ratio (Typ.)		5000:1		4,000:1		
Viewing Angle(H/V)		178/178		178/178		
Response Time (G-to-G)		6ms(Typ.)		8ms(Typ.)		
Display Colors		16.7M(True Display)		16.7M(True Display)		
Color Gamut		72%		72%		
Operation Hour		16/7		24/7		
Haze		2%		25%		
Speaker Type		Built in Speaker (15W + 15W)		Built in Speaker (10W + 10W)		
Input	RGB	D-Sub, DVI-D, Display Port 1.2 (2), Display Port 1.1 (1)		DVI-I(D-Sub Common), Display Port 1.2 (2) → Support UHD 60hz		
	VIDEO	HDMI 1.4 (3)		HDMI 1.4 (4)		
	HDCP	HDCP1.4 (→ support UHD 30hz)		HDCP1.4 (→ support UHD 30hz)		
	AUDIO	Stereo mini Jack, RGB, DVI, HDMI		Stereo mini Jack, RGB, DVI, HDMI		
	USB	USB (S/W update only)		USB (S/W update only)		
Output	AUDIO	Stereo Mini Jack		Stereo Mini Jack		
External Control		RS232C(in/out), RJ45		RS232C(in/out), RJ45		
External Sensor		IR		IR		
Power Type		Internal		Internal		
Power Supply		AC 100 - 240 V~ (+/- 10 %), 50/60 Hz		AC 100 - 240 V~ (+/- 10 %), 50/60 Hz		
VESA Mount		600x400mm		400x400mm	600x400mm	900x600mm
Protection Glass		Yes	No	No		
Stand Type		Foot Stand (Optional)		Foot Stand (Optional)		
Media Player		SBB		SBB		
Operating Temperature		0°C~ 40°C		0°C~ 40°C		
Humidity		10~80%		10~80%		
Feature	Highlight	All-in-one Touch UHD Smart Signage	UHD Smart Signage	UHD Smart Signage		
	H/W	Temperature Sensor, Clock Battery(80hrs Clock Keeping), Built in Speaker(15W 2ch), Video Wall(15x15(OSD))	Temperature Sensor, Pivot Display, Clock Battery(80hrs Clock Keeping), Built in Speaker(15W 2ch), Video Wall(15x15(OSD))	Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall(15x15(OSD)), IP5x		
	S/W	FHD 4 PBP Support (2/3/4 PBP), Auto Source Switching & Recovery, LFD Home UI, Button Lock, DDC CI, DHCP with RJ45 MDC Urgent Message by MDC, Hot key option, Plug&Play (Initial Setting)		FHD 4 PBP Support (2/3/4 PBP), Auto Source Switching & Recovery, LFD Home UI, Button Lock, DHCP with RJ45 MDC, Hot key option, Plug&Play (Initial Setting)		