

# STRETCHED DISPLAY



## STRETCHED RESOLUTION

Wide 16:4.5 displays deliver vibrant content even in tight spaces




## 24/7 OPERATION

Ongoing performance for transportation, retail and other high-demand venues



## AN UNPARALLELED VISUAL EXPERIENCE

High brightness and non-glare panel adjust image clarity to match various lighting conditions



## VIEWER-FRIENDLY DESIGN

Slim depth and narrow bezel maximize content space for added viewer engagement



## PIVOT MODE

Arrange displays in portrait or landscape format for optimal presentation

# SPECIFICATIONS

## | STRETCHED DISPLAY

SERIES		SHF
Size		37"
Resolution		1920x540 (16:4.5)
Brightness(Typ.)		700nit
Contrast Ratio(Typ.)		4000:1
Viewing Angle(H/V)		178:178
Response Time (G-to-G)		16ms
Display Colors		8bit - 16.7M
Color Gamut		72%
Operation Hour		24/7
Haze		44%
Speaker Type		N/A
Input	RGB	DVI-I, Display Port 1.2
	VIDEO	HDMI 1.4 (1)
	HDCP	HDCP 2.2
	AUDIO	Stereo mini Jack
	USB	USB 2.0 x1
Input	RGB	DP1.2(Loop-out)
	AUDIO	Stereo mini Jack
External Control		RS232C(in/out) thru Stereo mini Jack, RJ45
External Sensor		IR
Power Type		Internal
Power Supply		AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Dimension (mm)	Set	915.8 x 281.1 x 39.9
	Package	1102 X 122 X 369
Weight (kg)	Set	6.6kg
	Package	8.5kg
VESA Mount		400x200mm
Protection Glass		N/A
Stand Type		Foot Stand (Optional)
Bezel Width (mm)		5.7 (Side), 12 (Top/Bottom)
Operating Temperature		0°C~ 40°C
Humidity		10~80%
Key		Slim & Light LFD with Built-in MagicInfo Player S3, SSSP 3.0
Feature	H/W	USB Plug and Play, Tilting and Portrait Install support, Daisy Chains, Shock and Vibration certificated(IEC 61373)
	S/W	Magic Clone(to USB), RS232 MDC, , Video Wall, Smart Scheduling, Auto Source Switching, Internal Media Player